

Dated: January 10, 2005.

**Madeleine Clayton,**

*Management Analyst, Office of the Chief Information Officer.*

[FR Doc. 05-788 Filed 1-13-05; 8:45 am]

BILLING CODE 3510-06-P

## DEPARTMENT OF COMMERCE

### International Trade Administration

[A-588-824]

#### Notice of Final Results of Antidumping Duty Changed Circumstances Review and Revocation, In Part: Certain Corrosion-Resistant Carbon Steel Flat Products From Japan

**AGENCY:** Import Administration, International Trade Administration, Department of Commerce.

**EFFECTIVE DATE:** January 14, 2005.

**FOR FURTHER INFORMATION CONTACT:**

Christopher Hargett, George McMahon, or James Terpstra, AD/CVD Operations, Office 3, Import Administration, International Trade Administration, U.S. Department of Commerce, 14th Street and Constitution Avenue, NW., Washington, DC 20230; telephone (202) 482-4161, (202) 482-1167, or (202) 482-3965, respectively.

**SUPPLEMENTARY INFORMATION:**

#### Background

On August 19, 1993, the Department of Commerce (the Department) published an antidumping duty order on certain corrosion-resistant carbon steel flat products from Japan. *See Antidumping Duty Orders: Certain Corrosion-Resistant Carbon Steel Flat Products From Japan*, 58 FR 44163 (August 19, 1993). On October 5, 2004, SteelSummit International, Inc. (SteelSummit), an importer of certain corrosion-resistant carbon steel flat products (CORE) from Japan and an interested party in this proceeding, requested that the Department revoke the antidumping duty order on CORE from Japan with respect to nickel-plated steel foil through the initiation of a changed circumstances review.

According to SteelSummit, revocation with respect to nickel-plated steel foil is warranted because there is no longer any domestic interest in the continuation of the order with respect to the specified nickel-plated steel foil. The Department received letters from U.S. Steel Group (U.S. Steel) and International Steel Group (ISG) on November 1, 2004, and November 16, 2004, respectively, attesting to the lack of interest by the domestic industry regarding continuation of the order with

respect to the nickel-plated steel foil specified in SteelSummit's changed circumstances request.

In response to SteelSummit's request and based on the information provided by U.S. Steel and ISG, on November 26, 2004, the Department simultaneously initiated a changed circumstances review and issued a notice of preliminary intent to revoke the order, in part (69 FR 68876). The Department provided interested parties an opportunity to comment on our preliminary intent to revoke the order, in part, with respect to nickel-plated steel foil. We did not receive any comments. Therefore, the final results of review are not different from the preliminary results and we are revoking the order, in part, with respect to certain nickel-plated steel foil as described in the "Scope of the Order" section of this notice.

#### Scope of the Order

The products subject to this order include flat-rolled carbon steel products, of rectangular shape, either clad, plated, or coated with corrosion-resistant metals such as zinc, aluminum, or zinc-, aluminum-, nickel- or iron-based alloys, whether or not corrugated or painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating, in coils (whether or not in successively superimposed layers) and of a width of 0.5 inch or greater, or in straight lengths which, if of a thickness less than 4.75 millimeters, are of a width of 0.5 inch or greater and which measures at least 10 times the thickness or if of a thickness of 4.75 millimeters or more are of a width which exceeds 150 millimeters and measures at least twice the thickness, as currently classifiable in the Harmonized Tariff Schedule under item numbers: 7210.30.0030, 7210.30.0060, 7210.41.0000, 7210.49.0030, 7210.49.0090, 7210.61.0000, 7210.69.0000, 7210.70.6030, 7210.70.6060, 7210.70.6090, 7210.90.1000, 7210.90.6000, 7210.90.9000, 7212.20.0000, 7212.30.1030, 7212.30.1090, 7212.30.3000, 7212.30.5000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7212.60.0000, 7215.90.1000, 7215.90.3000, 7215.90.5000, 7217.20.1500, 7217.30.1530, 7217.30.1560, 7217.90.1000, 7217.90.5030, 7217.90.5060, and 7217.90.5090.

Included in the order are flat-rolled products of nonrectangular cross-section where such cross-section is achieved subsequent to the rolling process (*i.e.*, products which have been "worked

after rolling")—for example, products which have been bevelled or rounded at the edges.

Excluded from the scope of the order are flat-rolled steel products either plated or coated with tin, lead, chromium, chromium oxides, both tin and lead ("terne plate"), or both chromium and chromium oxides ("tin-free steel"), whether or not painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating. Also excluded from the scope of the order are certain clad stainless flat-rolled products, which are three-layered corrosion-resistant carbon steel flat-rolled products less than 4.75 millimeters in composite thickness that consist of a carbon steel flat-rolled product clad on both sides with stainless steel in a 20%-60%-20% ratio. *See Antidumping Duty Orders: Certain Corrosion-Resistant Carbon Steel Flat Products From Japan*, 58 FR 44163 (August 19, 1993).

Also excluded from the scope of this order are imports of certain corrosion-resistant carbon steel flat products meeting the following specifications: Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of chromate, and finally a layer consisting of silicate. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Antidumping Duty Administrative Review, and Revocation in Part of Antidumping Duty Order*, 62 FR 66848 (December 22, 1997).

Also excluded from the scope of this order are imports of subject merchandise meeting all of the following criteria: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer

consisting of chromate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of chromate, and finally a layer consisting of silicate. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Antidumping Duty Administrative Review, and Revocation in Part of Antidumping Duty Order*, 64 FR 14861 (March 29, 1999).

Also excluded from the scope of this order are: (1) Carbon steel flat products measuring 1.84 mm in thickness and 43.6 mm or 16.1 mm in width consisting of carbon steel coil (SAE 1008) clad with an aluminum alloy that is balance aluminum, 20% tin, 1% copper, 0.3% silicon, 0.15% nickel, less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys; and (2) carbon steel flat products measuring 0.97 mm in thickness and 20 mm in width consisting of carbon steel coil (SAE 1008) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9% to 11% tin, 9% to 11% lead, less than 1% zinc, less than 1% other materials and meeting the requirements of SAE standard 792 for bearing and bushing alloys, the second layer consisting of 45% to 55% lead, 38% to 50% PTFE, 3% to 5% molybdenum disulfide and less than 2% other materials. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 64 FR 57032 (October 22, 1999).

Also excluded from the scope of the order are imports of doctor blades meeting the following specifications: Carbon steel coil or strip, plated with nickel phosphorous, having a thickness of 0.1524 millimeters (0.006 inches), a width between 31.75 millimeters (1.25 inches) and 50.80 millimeters (2.00 inches), a core hardness between 580 to 630 HV, a surface hardness between 900–990 HV; the carbon steel coil or strip consists of the following elements identified in percentage by weight: 0.90% to 1.05% carbon; 0.15% to 0.35% silicon; 0.30% to 0.50% manganese; less than or equal to 0.03% of phosphorous; less than or equal to 0.006% of sulfur; other elements representing 0.24%; and the remainder of iron. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 65 FR 53983 (September 6, 2000).

Also excluded from the scope of the order are imports of carbon steel flat

products meeting the following specifications: Carbon steel flat products measuring 1.64 millimeters in thickness and 19.5 millimeters in width consisting of carbon steel coil (SAE 1008) with a lining clad with an aluminum alloy that is balance aluminum; 10 to 15% tin; 1 to 3% lead; 0.7 to 1.3% copper; 1.8 to 3.5% silicon; 0.1 to 0.7% chromium; less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 66 FR 8778 (February 2, 2001).

Also excluded from the scope of the order are carbon steel flat products meeting the following specifications: (1) Carbon steel flat products measuring 0.975 millimeters in thickness and 8.8 millimeters in width consisting of carbon steel coil (SAE 1012) clad with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9%–11% tin, 9%–11% lead, maximum 1% other materials and meeting the requirements of SAE standard 792 for Bearing and Bushing Alloys, the second layer consisting of 13%–17% carbon, 13%–17% aromatic polyester, with a balance (approx. 66%–74%) of polytetrafluorethylene (PTFE); and (2) carbon steel flat products measuring 1.02 millimeters in thickness and 10.7 millimeters in width consisting of carbon steel coil (SAE 1008) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9%–11% tin, 9%–11% lead, less than 0.35% iron, and meeting the requirements of SAE standard 792 for bearing and bushing alloys, the second layer consisting of 45%–55% lead, 3%–5% molybdenum disulfide, with a balance (approx. 40%–52%) of polytetrafluorethylene (PTFE). *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 66 FR 15075 (March 15, 2001).

Also excluded from this order are products meeting the following specifications: Carbon steel coil or strip, measuring 1.93 millimeters or 2.75 millimeters (0.076 inches or 0.108 inches) in thickness, 87.3 millimeters or 99 millimeters (3.437 inches or 3.900 inches) in width, with a low carbon steel back comprised of: Carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin,

1.7% lead, 0.3% antimony, 2.5% silicon, 1% maximum total other (including iron), and remainder aluminum. Also excluded from this order are products meeting the following specifications: Carbon steel coil or strip, clad with aluminum, measuring 1.75 millimeters (0.069 inches) in thickness, 89 millimeters or 94 millimeters (3.500 inches or 3.700 inches) in width, with a low carbon steel back comprised of: Carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 2.5% silicon, 0.3% antimony, 1% maximum total other (including iron), and remainder aluminum. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 66 FR 20967 (April 26, 2001).

Also excluded from this order are products meeting the following specifications: Carbon steel coil or strip, measuring a minimum of and including 1.10mm to a maximum of and including 4.90mm in overall thickness, a minimum of and including 76.00mm to a maximum of and including 250.00mm in overall width, with a low carbon steel back comprised of: Carbon under 0.10%, manganese under 0.40%, phosphorous under 0.04%, sulfur under 0.05%, and silicon under 0.05%; clad with aluminum alloy comprised of: Under 2.51% copper, under 15.10% tin, and remainder aluminum as listed on the mill specification sheet. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 67 FR 7356 (February 19, 2002).

Also excluded from this order are products meeting the following specifications: (1) Diffusion annealed, non-alloy nickel-plated carbon products, with a substrate of cold-rolled battery grade sheet ("CRBG") with both sides of the CRBG initially electrolytically plated with pure, unalloyed nickel and subsequently annealed to create a diffusion between the nickel and iron substrate, with the nickel plated coating having a thickness of 0–5 microns per side with one side equaling at least 2 microns; and with the nickel carbon sheet having a thickness of from 0.004" (0.10mm) to 0.030" (0.762mm) and conforming to the following chemical specifications (%): C <= 0.08; Mn <= 0.45; P <= 0.02; S <= 0.02; Al <= 0.15; and Si <= 0.10; and the following physical specifications:

Tensile = 65 KSI maximum; Yield = 32–55 KSI; Elongation = 18% minimum (aim 34%); Hardness = 85–150 Vickers; Grain Type = Equiaxed or Pancake; Grain Size (ASTM) = 7–12; Delta r value = aim less than +/-0.2; Lankford value = <= 1.2.; and (2) next generation diffusion-annealed nickel plate meeting the following specifications: (a) Nickel-graphite plated, diffusion annealed, tin-nickel plated carbon products, with a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed tin-nickel plated carbon steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of mixture of natural nickel and graphite then electrolytically plated on the top side of the strip of the nickel-tin alloy; having a coating thickness: Top side: nickel-graphite, tin-nickel layer <= 1.0 micrometers; tin layer only <= 0.05 micrometers, nickel-graphite layer only <= 0.2 micrometers, and bottom side: Nickel layer <= 1.0 micrometers; (b) nickel-graphite, diffusion annealed, nickel plated carbon products, having a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; with both sides of the cold rolled base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion between the nickel and the iron substrate; with an additional layer of natural nickel-graphite then electrolytically plated on the top side of the strip of the nickel plated steel strip; with the nickel-graphite, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having a coating thickness: top side: nickel-graphite, tin-nickel layer <= 1.0 micrometers; nickel-graphite layer <= 0.5 micrometers; bottom side: nickel layer <= 1.0 micrometers; (c) diffusion annealed nickel-graphite plated products, which are cold-rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; having the bottom side of the

base metal first electrolytically plated with natural nickel, and the top side of the strip then plated with a nickel-graphite composition; with the strip then annealed to create a diffusion of the nickel-graphite and the iron substrate on the bottom side; with the nickel-graphite and nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having coating thickness: top side: nickel-graphite layer <= 1.0 micrometers; bottom side: nickel layer <= 1.0 micrometers; (d) nickel-phosphorous plated diffusion annealed nickel plated carbon product, having a natural composition mixture of nickel and phosphorus electrolytically plated to the top side of a diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion of the nickel and iron substrate; another layer of the natural nickel-phosphorous then electrolytically plated on the top side of the nickel plated steel strip; with the nickel-phosphorous, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-phosphorous, nickel layer <= 1.0 micrometers; nickel-phosphorous layer <= 0.1 micrometers; bottom side : nickel layer <= 1.0 micrometers; (e) diffusion annealed, tin-nickel plated products, electrolytically plated with natural nickel to the top side of a diffusion annealed tin-nickel plated cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the cold rolled strip initially electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of natural nickel then electrolytically plated on the top side of the strip of the nickel-tin alloy; sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having coating thickness: Top side: nickel-tin-nickel combination layer <= 1.0 micrometers; tin layer only <= 0.05 micrometers; bottom side:

nickel layer <= 1.0 micrometers; and (f) tin mill products for battery containers, tin and nickel plated on a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel; then annealed to create a diffusion of the nickel and iron substrate; then an additional layer of natural tin electrolytically plated on the top side; and again annealed to create a diffusion of the tin and nickel alloys; with the tin-nickel, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-tin layer <= 1 micrometer; tin layer alone <= 0.05 micrometers; bottom side: nickel layer <= 1.0 micrometer. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 67 FR 47768 (July 22, 2002).

Also excluded from this order are products meeting the following specifications: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of phosphate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of phosphate, and finally a layer consisting of silicate. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 67 FR 57208 (September 9, 2002).

Also excluded from this order are products meeting the following specifications: (1) Flat-rolled products (provided for in HTSUS subheading 7210.49.00), other than of high-strength steel, known as "ASE Iron Flash" and either: (A) Having a base layer of zinc-based zinc-iron alloy applied by hot-dipping and a surface layer of iron-zinc alloy applied by electrolytic process, the weight of the coating and plating not over 40 percent by weight of zinc; or (B)

two-layer-coated corrosion-resistant steel with a coating composed of (a) a base coating layer of zinc-based zinc-iron alloy by hot-dip galvanizing process, and (b) a surface coating layer of iron-zinc alloy by electro-galvanizing process, having an effective amount of zinc up to 40 percent by weight, and (2) corrosion resistant continuously annealed flat-rolled products, continuous cast, the foregoing with chemical composition (percent by weight): Carbon not over 0.06 percent by weight, manganese 0.20 or more but not over 0.40, phosphorus not over 0.02, sulfur not over 0.023, silicon not over 0.03, aluminum 0.03 or more but not over 0.08, arsenic not over 0.02, copper not over 0.08 and nitrogen 0.003 or more but not over 0.008; and meeting the characteristics described below: (A) Products with one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a two-layer coating composed of a base nickel-iron-diffused coating layer and a surface coating layer of annealed and softened pure nickel, with total coating thickness for both layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with scanning

electron microscope (SEM) not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (B) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a four-layer coating composed of a base nickel-iron-diffused coating layer; with an inner middle coating layer of annealed and softened pure nickel, an outer middle surface coating layer of hard nickel and a topmost nickel-phosphorus-plated layer; with combined coating thickness for the four layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (C) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, luster-agent-added nickel which is not heat-treated; with combined coating thickness for all three layers of more

than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; or (D) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, pure nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 68 FR 19970 (April 23, 2003).

As a result of this review, also excluded from the scope of this order is merchandise meeting the following specifications:

Property	Specification
Base metal .....	Aluminum Killed, Continuous Cast, Carbon Steel SAE 1008.
Chemical composition .....	C: 0.08% max. Si: 0.03% max. Mn: 0.40% max. P: 0.020% max. S: 0.020% max.
Nominal thickness .....	0.054 millimeters.
Thickness tolerance .....	Minimum 0.0513 millimeters. Maximum 0.0567 millimeters.
Width .....	600 millimeters or greater.
Nickel plate .....	Min. 2.45 microns per side.

### Final Results of Review and Revocation of Antidumping Duty Order, in Part

Pursuant to sections 751(d)(1) and 782(h)(2) of the Tariff Act of 1930, as amended (the Act), the Department may revoke an antidumping or countervailing duty order based on a review under section 751(b) of the Act (*i.e.*, a changed circumstances review). Section 751(b)(1) of the Act requires a changed circumstances review to be conducted upon receipt of a request which shows changed circumstances sufficient to warrant a review.

In this case, based on the information provided by SteelSummit, and comments from U.S. Steel and ISG, the Department preliminarily found that the continued relief provided by the order with respect to nickel-plated steel foil

from Japan is no longer of interest to the domestic industry. We did not receive any comments. Therefore, the Department is revoking the order on CORE from Japan with regard to the products that meet the specifications detailed above.

We will instruct U.S. Customs and Border Protection (CBP) to liquidate without regard to antidumping duties all unliquidated entries of nickel-plated steel foil not subject to final results of an administrative review. The Department will further instruct CBP to refund with interest any estimated antidumping duties collected with respect to unliquidated entries of nickel-plated steel foil entered, or withdrawn from warehouse for consumption on or after the publication date of the final

results of this changed circumstances review, in accordance with section 778 of the Act and 19 CFR 351.222(g)(4).

This changed circumstances administrative review, partial revocation of the antidumping duty order and notice are in accordance with sections 751(b) and (d) and 782(h) of the Act and section 351.216(e) and 351.222(g) of the Department's regulations.

Dated: January 10, 2005.

**Joseph A. Spetrini,**  
*Acting Assistant Secretary for Import Administration.*

[FR Doc. E5-148 Filed 1-13-05; 8:45 am]

BILLING CODE 3510-DS-P