

IRAC Frequency Assignment Subcommittee process, NTIA will notify the Commission's International Bureau that the site is nearing operational status. Upon public notice from the International Bureau, all Ku-band VMES licensees shall cease operations in the 14.47–14.5 GHz band within the relevant geographic zone (160 kms for single-dish radio observatories and Very Large Array antenna systems and 50 kms for Very Long Baseline Array antenna systems) of the new RAS site until the licensees complete coordination for the new RAS facility. Licensees shall notify the International Bureau once they have completed coordination for the new RAS site and shall submit the coordination agreement to the Commission. Upon receipt of such notification from a licensee, the International Bureau will issue a public notice stating that the licensee may commence operations within the coordination zone in 30 days if no party opposed the operations. The VMES licensee then will be permitted to commence operations in the 14.47–14.5 GHz band within the relevant coordination distance around the new RAS site, subject to any operational constraints developed in the coordination process.

(e) VMES licensees shall use Global Positioning Satellite-related or other similar position location technology to ensure compliance with paragraphs (c) and (d) of this section.

[74 FR 57099, Nov. 4, 2009]

§§ 25.227–25.249 [Reserved]

§ 25.250 Sharing between NGSO MSS Feeder links Earth Stations in the 19.3–19.7 GHz and 29.1–29.5 GHz Bands.

(a) NGSO MSS applicants shall be licensed to operate in the 29.1–29.5 GHz band for Earth-to-space transmissions and 19.3–19.7 GHz for space-to-Earth transmissions from feeder link earth station complexes. A “feeder link earth station complex” may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by NGSO-MSS licensees or applicants.

(b) Licensees of NGSO MSS feeder link earth stations separated by 800 km or less are required to coordinate their operations, see § 25.203. The results of the coordination shall be reported to the Commission.

[61 FR 44181, Aug. 28, 1996]

§ 25.251 Special requirements for coordination.

(a) The administrative aspects of the coordination process are set forth in § 101.103 of this chapter in the case of coordination of terrestrial stations with earth stations, and in § 25.203 in the case of coordination of earth stations with terrestrial stations.

(b) The technical aspects of coordination are based on Appendix S7 of the International Telecommunication Union Radio Regulations and certain recommendations of the ITU Radiocommunication Sector (available at the FCC's Reference Information Center, Room CY-A257, 445 12th Street, SW., Washington, DC 20554).

[66 FR 10630, Feb. 16, 2001]

§ 25.252 Special requirements for ancillary terrestrial components operating in the 2000–2020 MHz/2180–2200 MHz bands.

(a) Applicants for an ancillary terrestrial component in these bands must demonstrate that ATC base stations shall not:

(1) Exceed an EIRP of -100.6 dBW/4 kHz for out-of-channel emissions at the edge of the MSS licensee's selected assignment.

(2) Exceed a peak EIRP of 27 dBW in 1.23 MHz.

(3) Exceed an EIRP toward the physical horizon (not to include man-made structures) of 25.5 dBW in 1.23 MHz.

(4) Be located less than 190 meters from all airport runways and aircraft stand areas, including takeoff and landing paths.

(5) Exceed an aggregate power flux density of -51.8 dBW/m² in a 1.23 MHz bandwidth at all airport runways and aircraft stand areas, including takeoff and landing paths and all ATC base station antennas shall have an overhead gain suppression according to the following.

§ 25.252

47 CFR Ch. I (10–1–10 Edition)

(6) Be located less than 820 meters from a U.S. Earth Station facility operating in the 2200–2290 MHz band. In its MSS ATC application, the MSS licensee should request a list of operational stations in the 2200–2290 MHz band.

(7) Generate EIRP density, averaged over any two millisecond active transmission interval, greater than -70 dBW/MHz in the 1559–1610 MHz band. The EIRP, measured over any two millisecond active transmission interval, of discrete out-of-band emissions of less than 700 Hz bandwidth from such base

stations, shall not exceed -80 dBW in the 1559–1610 MHz band. A root-mean-square detector function with a resolution bandwidth of one megahertz or equivalent and no less video bandwidth shall be used to measure wideband EIRP density for purposes of this rule, and narrowband EIRP shall be measured with a root-mean-square detector function with a resolution bandwidth of one kilohertz or equivalent.

(8) Use ATC base station antennas that have a gain greater than 17 dBi and must have an overhead gain suppression according to the following:

Angle from direction of maximum gain, in vertical plane, above antenna (degrees)	Antenna discrimination pattern (dB)
0	G _{max}
2	Not to Exceed G _{max} - 14
8 to 180	Not to Exceed G _{max} - 25

Where: G_{max} is the maximum gain of the base station antenna in dBi.

(b) Applicants for an ancillary terrestrial component in these bands must demonstrate that ATC mobile terminals shall:

(1) Observe a peak EIRP limit of 1.0 dBW in 1.23 MHz.

(2) Limit out-of-channel emissions at the edge of a MSS licensee's selected assignment to an EIRP density of -67 dBW/4 kHz.

(3) Not generate EIRP density, averaged over any two-millisecond active transmission interval, greater than -70 dBW/MHz in the 1559–1610 MHz band. The EIRP, measured over any two-millisecond active transmission interval, of discrete out-of-band emissions of less than 700 Hz bandwidth from such mobile terminals shall not exceed -80 dBW in the 1559–1610 MHz band. The EIRP density of carrier-off-state emissions from such mobile terminals shall not exceed -80 dBW/MHz in the 1559–1610 MHz band, averaged over a two-millisecond interval. A root-mean-square detector function with a resolution bandwidth of one megahertz or equivalent and no less video bandwidth shall be used to measure wideband EIRP density for purposes of this rule, and narrowband EIRP shall be measured with a root-mean-square detector function with a resolution bandwidth of one kilohertz or equivalent.

(c) For ATC operations in the 2000–2020 MHz band, the power of any emis-

sion outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency within the 2000 to 2020 MHz band outside the licensee's frequency band(s) of operations, emissions shall be attenuated by at least $43 + 10 \log(P)$ dB.

(2) Emissions on frequencies lower than 1995 MHz and higher than 2025 MHz shall be attenuated by at least $70 + 10 \log P$. Emissions in the bands 1995–2000 MHz and 2020–2025 MHz shall be attenuated by at least a value as determined by linear interpolation from $70 + 10 \log P$ at 1995 MHz or 2025 MHz, to $43 + 10 \log P$ dB at the nearest MSS band edge at 2000 MHz or 2020 MHz respectively.

(3) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, in its discretion, require greater attenuation than specified in paragraphs (c)(1) and (2) of this section.

(4) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater.

NOTE TO § 25.252: The preceding rules of § 25.252 are based on cdma2000 system architecture. To the extent that a 2 GHz MSS licensee is able to demonstrate that the use of a different system architecture would produce no greater potential interference than that produced as a result of implementing the rules of this section, an MSS licensee is permitted to apply for ATC authorization based on another system architecture.

[68 FR 33651, June 5, 2003, as amended at 70 FR 19318, Apr. 13, 2005]

§ 25.253 Special requirements for ancillary terrestrial components operating in the 1626.5–1660.5 MHz/1525–1559 MHz bands.

(a) An ancillary terrestrial component in these bands shall:

(1) In any band segment coordinated for the exclusive use of an MSS applicant within the land area of the U.S., where there is no other L-Band MSS satellite making use of that band segment within the visible portion of the geostationary arc as seen from the ATC coverage area, the ATC system will be limited by the in-band and out-of-band emission limitations contained in this section and the requirement to maintain a substantial MSS service.

(2) In any band segment that is coordinated for the shared use of the applicant's MSS system and another MSS operator, where the coordination agreement existed prior to February 10, 2005 and permits a level of interference to the other MSS system of less than 6% $\Delta T/T$, the applicant's combined ATC and MSS operations shall increase the system noise level of the other MSS to no more than 6% $\Delta T/T$. Any future coordination agreement between the parties governing ATC operation will supersede this paragraph.

(3) In any band segment that is coordinated for the shared use of the applicant's MSS system and another MSS operator, where a coordination agreement existed prior to February 10, 2005 and permits a level of interference to the other MSS system of 6% $\Delta T/T$ or greater, the applicant's ATC operations may increase the system noise level of the other MSS system by no more than an additional 1% $\Delta T/T$. Any future coordination agreement between the parties governing ATC operations will supersede this paragraph.

(4) In a band segment in which the applicant has no rights under a coordination agreement, the applicant may not implement ATC in that band.

(b) ATC base stations shall not exceed an out-of-channel emissions measurement of -57.9 dBW/MHz at the edge of a MSS licensee's authorized and internationally coordinated MSS frequency assignment.

(c) An applicant for an ancillary terrestrial component in these bands shall:

(1) Demonstrate, at the time of application, how its ATC network will comply with the requirements of footnotes US308 and US315 to the table of frequency allocations contained in § 2.106 of this chapter regarding priority and preemptive access to the L-band MSS spectrum by the aeronautical mobile-satellite en-route service (AMS(R)S) and the global maritime distress and safety system (GMDSS).

(2) Coordinate with the terrestrial CMRS operators prior to initiating ATC transmissions when co-locating ATC base stations with terrestrial commercial mobile radio service (CMRS) base stations that make use of Global Positioning System (GPS) time-based receivers.

(3) Provide, at the time of application, calculations that demonstrate the ATC system conforms to the $\Delta T/T$ requirements in paragraphs (a)(2) and (a)(3) of this section, if a coordination agreement that incorporates the ATC operations does not exist with other MSS operators.

(d) Applicants for an ancillary terrestrial component in these bands must demonstrate that ATC base stations shall not:

(1) Exceed a peak EIRP of $31.9-10 \cdot \log(\text{number of carriers})$ dBW/200kHz, per sector, for each carrier in the 1525–1541.5 MHz and 1547.5–1559 MHz frequency bands;

(2) Exceed an EIRP in any direction toward the physical horizon (not to include man-made structures) of $26.9-10 \cdot \log(\text{number of carriers})$ dBW/200 kHz, per sector, for each carrier in the 1525–1541.5 MHz and 1547.5–1559 MHz frequency bands;

(3) Exceed a peak EIRP of $23.9-10 \cdot \log(\text{number of carriers})$ dBW/200