

Federal Communications Commission

§ 18.307

| ISM frequency | Tolerance |
|------------------|------------|
| 915 MHz | ±13.0 MHz |
| 2,450 MHz | ±50.0 MHz |
| 5,800 MHz | ±75.0 MHz |
| 24,125 MHz | ±125.0 MHz |
| 61.25 GHz | ±250.0 MHz |
| 122.50 GHz | ±500.0 MHz |
| 245.00 GHz | ±1.0 GHz |

NOTE: The use of the 6.78 MHz ±15 kHz frequency band is subject to the conditions of footnote 524 of the Table of Allocations. See § 2.106.

§ 18.303 Prohibited frequency bands.

Operation of ISM equipment within the following safety, search and rescue

frequency bands is prohibited: 490–510 kHz, 2170–2194 kHz, 8354–8374 kHz, 121.4–121.6 MHz, 156.7–156.9 MHz, and 242.8–243.2 MHz.

§ 18.305 Field strength limits.

(a) ISM equipment operating on a frequency specified in § 18.301 is permitted unlimited radiated energy in the band specified for that frequency.

(b) The field strength levels of emissions which lie outside the bands specified in § 18.301, unless otherwise indicated, shall not exceed the following:

| Equipment | Operating frequency | RF Power generated by equipment (watts) | Field strength limit (uV/m) | Distance (meters) |
|--|--------------------------|---|--------------------------------|--------------------------|
| Any type unless otherwise specified (miscellaneous). | Any ISM frequency | Below 500 | 25 | 300 |
| | | 500 or more | 25×SQRT(power/500) | 1300 |
| Industrial heaters and RF stabilized arc welders. | On or below 5,725 MHz .. | Any non-ISM frequency .. | Below 500 | 300 |
| | | | 500 or more | 15×SQRT(power/500) |
| Medical diathermy | Above 5,725 MHz | Any | 10 | 1,600 |
| | | | Any | (²) |
| Ultrasonic | Below 490 kHz | Any ISM frequency | 25 | 300 |
| | | Any non-ISM frequency .. | Any | 15 |
| Induction cooking ranges | 490 to 1,600 kHz | Below 500 | 2,400/F(kHz) | 300 |
| | | 500 or more | 2,400/F(kHz)× SQRT(power/500). | ³ 300 |
| | | Any | 24,000/F(kHz) | 30 |
| | | Any | 15 | 30 |
| Induction cooking ranges | Below 90 kHz | Any | 1,500 | 130 |
| | | Any | 300 | 430 |
| | | On or above 90 kHz | Any | 300 |

¹ Field strength may not exceed 10 uV/m at 1600 meters. Consumer equipment operating below 1000 MHz is not permitted the increase in field strength otherwise permitted here for power over 500 watts.
² Reduced to the greatest extent possible.
³ Field strength may not exceed 10 uV/m at 1600 meters. Consumer equipment is not permitted the increase in field strength otherwise permitted here for over 500 watts.
⁴ Induction cooking ranges manufactured prior to February 1, 1980, shall be subject to the field strength limits for miscellaneous ISM equipment.

(c) The field strength limits for RF lighting devices shall be the following:

| Frequency (MHz) | Field strength limit at 30 meters (uV/m) |
|-------------------------|--|
| Non-consumer equipment: | |
| 30–88 | 30 |
| 88–216 | 50 |
| 216–1000 | 70 |
| Consumer equipment: | |
| 30–88 | 10 |
| 88–216 | 15 |
| 216–1000 | 20 |

NOTES

- The tighter limit shall apply at the boundary between two frequency ranges.
- Testing for compliance with these limits may be made at closer distances, provided a sufficient number of measurements are taken to plot the radiation pattern, to deter-

mine the major lobes of radiation, and to determine the expected field strength level at 30, 300, or 1600 meters. Alternatively, if measurements are made at only one closer fixed distance, then the permissible field strength limits shall be adjusted using 1/d as an attenuation factor.

[50 FR 36070, Sept. 5, 1985, as amended at 51 FR 17970, May 16, 1986; 52 FR 43197, Nov. 10, 1987]

§ 18.307 Conduction limits.

For the following equipment, when designed to be connected to the public utility (AC) power line the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies shall not exceed the limits in the following tables. Compliance with the provisions of this