

## § 18.212

after a grant has been issued by the FCC for the basic device, the application may, in lieu of the report of measurements, be accompanied by a statement including:

(1) FCC Identifier of device for which measurements are on file with the FCC.

(2) Date when equipment authorization was granted for the device(s) listed under paragraph (c)(1) of this section and the file number of such grant.

(3) Description of the difference between the device listed under paragraph (c)(1) of this section and the additional device(s).

(4) A statement that the report of measurements filed for the device listed under paragraph (c)(1) of this section applies also to the additional device(s).

(5) Photographs pursuant to § 2.1033(c).

### § 18.212 Compliance information.

(a) Equipment authorized under the Declaration of Conformity procedure shall include the following compliance information in lieu of the information required by § 2.1077.

(1) Identification of the product, e.g., name and model number.

(2) A statement similar to the following:

*This device complies with Part 18 of the FCC Rules.*

(3) The name and address of the responsible party as defined in § 2.909 of the rules. This party must be located within the United States.

(b) The compliance information may be placed in the instruction manual, on a separate sheet, or on the packaging. There is no specific format for this information.

[63 FR 36603, July 7, 1998]

### § 18.213 Information to the user.

Information on the following matters shall be provided to the user in the instruction manual or on the packaging if an instruction manual is not provided for any type of ISM equipment:

(a) The interference potential of the device or system

(b) Maintenance of the system

## 47 CFR Ch. I (10–1–15 Edition)

(c) Simple measures that can be taken by the user to correct interference.

(d) Manufacturers of RF lighting devices must provide an advisory statement, either on the product packaging or with other user documentation, similar to the following: This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45–30 MHz. Variations of this language are permitted provided all the points of the statement are addressed and may be presented in any legible font or text style.

[50 FR 36069, Sept. 5, 1985, as amended at 51 FR 17970, May 16, 1986; 64 FR 37419, July 12, 1999]

## Subpart C—Technical Standards

### § 18.301 Operating frequencies.

ISM equipment may be operated on any frequency above 9 kHz except as indicated in § 18.303. The following frequency bands, in accordance with § 2.106 of the rules, are allocated for use by ISM equipment:

ISM frequency	Tolerance
6.78 MHz .....	±15.0 kHz
13.56 MHz .....	±7.0 kHz
27.12 MHz .....	±163.0 kHz
40.68 MHz .....	±20.0 kHz
915 MHz .....	±13.0 MHz
2,450 MHz .....	±50.0 MHz
5,800 MHz .....	±75.0 MHz
24,125 MHz .....	±125.0 MHz
61.25 GHz .....	±250.0 MHz
122.50 GHz .....	±500.0 MHz
245.00 GHz .....	±1.0 GHz

NOTE: The use of the 6.78 MHz ±15 kHz frequency band is subject to the conditions of footnote 524 of the Table of Allocations. See § 2.106.

### § 18.303 Prohibited frequency bands.

Operation of ISM equipment within the following safety, search and rescue frequency bands is prohibited: 490–510 kHz, 2170–2194 kHz, 8354–8374 kHz, 121.4–121.6 MHz, 156.7–156.9 MHz, and 242.8–243.2 MHz.

### § 18.305 Field strength limits.

(a) ISM equipment operating on a frequency specified in § 18.301 is permitted