

§ 10.520

§ 10.520 Common audio attention signal.

A Participating CMS Provider and equipment manufacturers may only market devices for public use under part 10 that include an audio attention signal that meets the requirements of this section.

(a) The audio attention signal must have a temporal pattern of one long tone of two (2) seconds, followed by two short tones of one (1) second each, with a half (0.5) second interval between each tone. The entire sequence must be repeated twice with a half (0.5) second interval between each repetition.

(b) For devices that have polyphonic capabilities, the audio attention signal must consist of the fundamental frequencies of 853 Hz and 960 Hz transmitted simultaneously.

(c) For devices with only a monophonic capability, the audio attention signal must be 960 Hz.

(d) The audio attention signal must be restricted to use for Alert Messages under part 10.

(e) A device may include the capability to mute the audio attention signal.

§ 10.530 Common vibration cadence.

A Participating CMS Provider and equipment manufacturers may only market devices for public use under part 10 that include a vibration cadence capability that meets the requirements of this section.

(a) The vibration cadence must have a temporal pattern of one long vibration of two (2) seconds, followed by two short vibrations of one (1) second each, with a half (0.5) second interval between each vibration. The entire sequence must be repeated twice with a half (0.5) second interval between each repetition.

(b) The vibration cadence must be restricted to use for Alert Messages under part 10.

(c) A device may include the capability to mute the vibration cadence.

47 CFR Ch. I (10–1–16 Edition)

§ 10.540 Attestation requirement. [Reserved]

PART 11—EMERGENCY ALERT SYSTEM (EAS)

Subpart A—General

Sec.

- 11.1 Purpose.
- 11.2 Definitions.
- 11.11 The Emergency Alert System (EAS).
- 11.12–11.14 [Reserved]
- 11.15 EAS Operating Handbook.
- 11.16 National Control Point Procedures.
- 11.18 EAS Designations.
- 11.20 State Relay Network.
- 11.21 State and Local Area plans and FCC Mapbook.

Subpart B—Equipment Requirements

- 11.31 EAS protocol.
- 11.32 EAS Encoder.
- 11.33 EAS Decoder.
- 11.34 Acceptability of the equipment.
- 11.35 Equipment operational readiness.

Subpart C—Organization

- 11.41 Participation in EAS.
- 11.42 [Reserved]
- 11.43 National level participation.
- 11.44 [Reserved]
- 11.45 Prohibition of false or deceptive EAS transmissions.
- 11.46 EAS public service announcements.
- 11.47 Optional use of other communications methods and systems.

Subpart D—Emergency Operations

- 11.51 EAS code and Attention Signal Transmission requirements.
- 11.52 EAS code and Attention Signal Monitoring requirements.
- 11.53 [Reserved]
- 11.54 EAS operation during a National Level emergency.
- 11.55 EAS operation during a State or Local Area emergency.
- 11.56 Obligation to process CAP-formatted EAS messages.

Subpart E—Tests

- 11.61 Tests of EAS procedures.

AUTHORITY: 47 U.S.C. 151, 154 (i) and (o), 303(r), 544(g) and 606.

SOURCE: 59 FR 67092, Dec. 28, 1994, unless otherwise noted.