

Federal Communications Commission

§ 22.725

either service to be “cut off” (excluded from a same-day filing group) and dismissed, pursuant to § 22.131(c)(3)(ii) and § 22.131(c)(4).

[59 FR 59956, Nov. 21, 1994, as amended at 62 FR 11636, Mar. 12, 1997]

§ 22.719 Additional channel policy for rural radiotelephone stations.

The rules in this section govern the processing of applications for central office stations that request a rural radiotelephone channel pair when the applicant has applied for or been granted an authorization for other rural radiotelephone channel pairs in the same area. The general policy of the FCC is to promote effective use of the spectrum by encouraging the use of spectrum-efficient technologies (i.e. BETRS) and by assigning the minimum number of channels necessary to provide service.

(a) *Transmitters in same area.* Any central office station transmitter on any channel pair listed in § 22.725 is considered to be in the same area as another central office station transmitter on any other channel pair listed in § 22.725 if the transmitting antennas are located within 10 kilometers (6.2 miles) of each other.

(b) *Initial channel pairs.* The FCC does not assign more than two channel pairs for new central office stations, unless there are more than eight rural subscriber stations to be served. Stations are considered to be new if there are no authorized transmitters on any channel listed in § 22.725 controlled by the applicant in the same geographic area.

(c) *Additional channel pairs.* Applications for central office station transmitters to be located in the same area as an authorized central office station controlled by the applicant, but to operate on a different channel pair(s) are considered as requests for additional channel pair(s) for the authorized central office station. The FCC may grant applications for additional channel pairs provided that the need for each additional channel pair (after the first two) is established and fully justified in terms of achieving the required grade of service (blocking probability), and the applicant demonstrates that there will still be adequate spectrum available in the area to meet realistic

estimates of current and future demand for paging, two-way mobile and rural radiotelephone services. In the case of conventional rural radiotelephone central office stations, an explanation must be provided as to why BETRS technology is not being used instead of additional channel pairs.

CONVENTIONAL RURAL RADIOTELEPHONE STATIONS

§ 22.721 Geographic area authorizations.

Eligible persons may apply for a paging geographic area authorization in the Rural Radiotelephone Service, on the channel pairs listed in § 22.725, by following the procedures and requirements set forth in § 22.503 for paging geographic area authorizations.

[62 FR 11636, Mar. 12, 1997]

§ 22.723 Secondary site-by-site authorizations.

Authorizations for new facilities (including new sites and additional channel pairs for existing sites) in the Rural Radiotelephone Service (including BETRS facilities) may be granted after May 12, 1997 only on the condition that such authorizations shall be secondary to any existing or future co-channel paging geographic area authorization in the Paging and Radiotelephone Service or the Rural Radiotelephone Service. If the paging geographic area licensee notifies the Rural Radiotelephone Service licensee that operation of a co-channel secondary facility must be discontinued because it may cause interference to existing or planned facilities, the Rural Radiotelephone Service licensee must discontinue operation of that facility on the particular channel pair involved no later than six months after such notice.

[62 FR 11636, Mar. 12, 1997]

§ 22.725 Channels for conventional rural radiotelephone stations and basic exchange telephone radio systems.

The following channels are allocated for paired assignment to transmitters that provide conventional rural radiotelephone service and to transmitters

§ 22.727

in basic exchange telephone radio systems. These channels may be assigned for use by central office or rural subscriber stations as indicated, and inter-office stations. These channels may be assigned also for use by relay stations in systems where it would be impractical to provide rural radiotelephone service without the use of relay stations. All channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

Central office	Rural subscriber	Central office	Rural subscriber
VHF Channels			
152.03	158.49	152.57	157.83
152.06	158.52	152.60	157.86
152.09	158.55	152.63	157.89
152.12	158.58	152.66	157.92
152.15	158.61	152.69	157.95
152.18	158.64	152.72	157.98
152.21	158.67	152.75	158.01
152.51	157.77	152.78	158.04
152.54	157.80	152.81	158.07
UHF Channels			
454.025	459.025	454.350	459.350
454.050	459.050	454.375	459.375
454.075	459.075	454.400	459.400
454.100	459.100	454.425	459.425
454.125	459.125	454.450	459.450
454.150	459.150	454.475	459.475
454.175	459.175	454.500	459.500
454.200	459.200	454.525	459.525
454.225	459.225	454.550	459.550
454.250	459.250	454.575	459.575
454.275	459.275	454.600	459.600
454.300	459.300	454.625	459.625
454.325	459.325	454.650	459.650

(a) The channels listed in this section are also allocated for assignment in the Paging and Radiotelephone Service.

(b) In Puerto Rico and the Virgin Islands, channels in the 154.04–154.46 MHz and 161.40–161.85 MHz frequency ranges may be assigned to transmitters providing rural radiotelephone service; channels in these ranges are also allocated for assignment in the International Fixed Public and Aeronautical Fixed radio services.

[59 FR 59507, Nov. 17, 1994; 60 FR 9891, Feb. 22, 1995, as amended at 70 FR 19309, Apr. 13, 2005]

§ 22.727 Power limits for conventional rural radiotelephone transmitters.

The transmitting power of transmitters operating on the channels listed in

47 CFR Ch. I (10–1–16 Edition)

§ 22.725 must not exceed the limits in this section.

(a) *Maximum ERP.* The effective radiated power (ERP) of central office and rural subscriber station transmitters must not exceed the applicable limits in this paragraph under any circumstances.

Frequency range (MHz)	Maximum ERP (watts)
152–153	1400
157–159	150
454–455	3500
459–460	150

(b) *Basic power limit.* Except as provided in paragraph (d) of this section, the ERP of central office station transmitters must not exceed 500 Watts.

(c) *Height-power limits.* Except as provided in paragraph (d) of this section, the ERP of central office station transmitters must not exceed the amount that would result in an average distance to the “service contour” of 41.6 kilometers (26 miles) for VHF channels or 30.7 kilometers (19 miles) for UHF channels. The average distance to the “service contour” is calculated by taking the arithmetic mean of the distances determined using the procedures specified in § 22.567 for the eight cardinal radial directions, excluding cardinal radial directions for which 90% or more of the distance so calculated is over water.

(d) *Encompassed interfering contour areas.* Central office station transmitters are exempt from the basic power and height-power limits of this section if the area within their interfering contours is totally encompassed by the interfering contours of operating co-channel central office station transmitters controlled by the same licensee. For the purpose of this paragraph, operating transmitters are authorized transmitters that are providing service to subscribers.

(e) *Adjacent channel protection.* The ERP of central office station transmitters must not exceed 500 Watts if they transmit on channel 454.025 MHz and are located less than 7 kilometers (4.3 miles) from any Private Radio Services station receiving on adjacent channel 454.000 MHz.

[59 FR 59507, Nov. 17, 1994, as amended at 70 FR 19309, Apr. 13, 2005]