

Federal Communications Commission

§ 11.52

back and forth between automatic and manual operation.

(p) The standard required in this section is incorporated by reference into this section with the approval of the Director of the Federal Register under 5 U.S.C. 552(a) and 1 CFR part 51. To enforce any edition other than that specified in this section, the Federal Communications Commission must publish notice of change in the FEDERAL REGISTER and the material must be available to the public. All approved material is available for inspection at the Federal Communications Commission, 445 12th Street, SW., Washington, DC (Reference Information Center) and is available from the source indicated below. It is also available for inspection at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030 or go to http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html.

(1) The following standard is available from the EAS-CAP Industry Group (ECIG), 21010 Southbank Street, #365, Sterling, VA, 20165, go to <http://www.eas-cap.org>.

(i) “ECIG Recommendations for a CAP EAS Implementation Guide, Version 1.0” (May 17, 2010).

(ii) [Reserved]

[70 FR 71035, Nov. 25, 2005, as amended at 71 FR 76220, Dec. 20, 2006; 72 FR 62135, Nov. 2, 2007; 71 FR 76220, Dec. 20, 2006; 72 FR 62135, Nov. 2, 2007; 77 FR 16704, Mar. 22, 2012; 80 FR 37175, June 30, 2015]

§ 11.52 EAS code and Attention Signal Monitoring requirements.

(a) EAS Participants must be capable of receiving the Attention Signal required by § 11.31(a)(2) and emergency messages of other broadcast stations during their hours of operation. EAS Participants must install and operate during their hours of operation, equipment that is capable of receiving and decoding, either automatically or manually, the EAS header codes, emergency messages and EOM code, and which complies with the requirements in § 11.56.

NOTE TO PARAGRAPH (a): The two-tone Attention Signal will not be used to actuate

two-tone decoders but will be used as an aural alert signal.

(b) If manual interrupt is used as authorized in § 11.51(m)(2), decoders must be located so that operators at their normal duty stations can be alerted immediately when EAS messages are received.

(c) EAS Participants that are co-owned and co-located with a combined studio or control facility (such as an AM and FM licensed to the same entity and at the same location or a cable headend serving more than one system) may comply with the EAS monitoring requirements contained in this section for the combined station or system with one EAS Decoder. The requirements of § 11.33 must be met by the combined facility.

(d) EAS Participants must comply with the following monitoring requirements:

(1) With respect to monitoring for EAS messages that are formatted in accordance with the EAS Protocol, EAS Participants must monitor two EAS sources. The monitoring assignments of each broadcast station and cable system and wireless cable system are specified in the State EAS Plan and FCC Mapbook. They are developed in accordance with FCC monitoring priorities.

(2) With respect to monitoring EAS messages formatted in accordance with the specifications set forth in § 11.56(a)(2), EAS Participants' EAS equipment must interface with the Federal Emergency Management Agency's Integrated Public Alert and Warning System (IPAWS) to enable (whether through “pull” interface technologies, such as Really Simple Syndication (RSS) and Atom Syndication Format (ATOM), or “push” interface technologies, such as instant messaging and email) the distribution of Common Alert Protocol (CAP)-formatted alert messages from the IPAWS system to EAS Participants' EAS equipment.

(3) If the required EAS message sources cannot be received, alternate arrangements or a waiver may be obtained by written request to the Chief, Public Safety and Homeland Security Bureau. In an emergency, a waiver may

§ 11.53

be issued over the telephone with a follow up letter to confirm temporary or permanent reassignment.

(4) The management of EAS Participants shall determine which header codes will automatically interrupt their programming for State and Local Area emergency situations affecting their audiences.

(e) EAS Participants are required to interrupt normal programming either automatically or manually when they receive an EAS message in which the header code contains the Event codes for Emergency Action Notification (EAN), the National Periodic Test (NPT), or the Required Monthly Test (RMT) for their State or State/county location.

(1) *Automatic* interrupt of programming is required when facilities are unattended. Automatic operation must provide a permanent record of the EAS message that contains at a minimum the following information: Originator, Event, Location and valid time period of the message.

(2) Manual interrupt of programming and transmission of EAS messages may be used. EAS messages with the EAN Event code, or the NPT Event code in the case of a nationwide test of the EAS, must be transmitted immediately; Monthly EAS test messages must be transmitted within 60 minutes. All actions must be logged and recorded as specified in §§11.35(a) and 11.54(a)(3). Decoders must be programmed for the EAN Event header code and the RMT and RWT Event header codes (for required monthly and weekly tests), with the appropriate accompanying State and State/county location codes.

[70 FR 71036, Nov. 25, 2005, as amended at 77 FR 16705, Mar. 22, 2012; 80 FR 37176, June 30, 2015; 83 FR 37759, Aug. 2, 2018]

§ 11.53 [Reserved]

§ 11.54 EAS operation during a National Level emergency.

(a) Immediately upon receipt of an EAN message, or the NPT Event code in the case of a nationwide test of the EAS, EAS Participants must comply with the following requirements, as applicable:

47 CFR Ch. I (10–1–19 Edition)

(1) Analog and digital broadcast stations may transmit their call letters and analog cable systems, digital cable systems and wireless cable systems may transmit the names of the communities they serve during an EAS activation. State and Local Area identifications must be given as provided in State and Local Area EAS Plans.

(2) Analog and digital broadcast stations are exempt from complying with §§73.62 and 73.1560 of this chapter (operating power maintenance) while operating under this part.

(3) The time of receipt of the EAN shall be entered by analog and digital broadcast stations in their logs (as specified in §§73.1820 and 73.1840 of this chapter), by analog and digital cable systems in their records (as specified in §76.1711 of this chapter), by subject wireless cable systems in their records (as specified in §21.304 of this chapter), and by all other EAS Participants in their records as specified in §11.35(a).

(b) EAS Participants originating emergency communications under this section shall be considered to have conferred rebroadcast authority, as required by section 325(a) of the Communications Act of 1934, 47 U.S.C. 325(a), to other EAS Participants.

(c) During a national level EAS emergency, EAS Participants may transmit in lieu of the EAS audio feed an audio feed of the President's voice message from an alternative source, such as a broadcast network audio feed.

[77 FR 16705, Mar. 22, 2012, as amended at 80 FR 37177, June 30, 2015]

§ 11.55 EAS operation during a State or Local Area emergency.

(a) The EAS may be activated at the State and Local Area levels by EAS Participants at their discretion for day-to-day emergency situations posing a threat to life and property. Examples of natural emergencies which may warrant state EAS activation are: Tornadoes, floods, hurricanes, earthquakes, heavy snows, icing conditions, widespread fires, etc. Man-made emergencies warranting state EAS activation may include: Toxic gas leaks or liquid spills, widespread power failures, industrial explosions, and civil disorders.