

each of the bands. Measurements for conducted emissions caused by sources internal to the device are to be made in a shielded room. Measurements for conducted emissions caused by external signal sources shall be made in an ambient RF field whose field strength is 100 mV/m, following the same test conditions as described in paragraph (c)(3) of this section.

(d) The field strength of radiated emissions from cable ready consumer electronics equipment shall not exceed the limits in §15.109(a) when measured in accordance with the applicable procedures specified in §§15.31 and 15.35 for unintentional radiators, with the following modifications. During testing the NTSC input signal level is to be +15 dBmV, with a visual to aural ratio of 10 dB. The visual carrier is to be modulated by a 10 IRE flat field with color burst; the aural carrier is to be unmodulated. Measurements are to be taken on six EIA IS-132 channels evenly spaced across the required RF input range of the equipment under test.

[59 FR 25341, May 16, 1994, as amended at 61 FR 18509, Apr. 26, 1996; 65 FR 64391, Oct. 27, 2000; 68 FR 68546, Dec. 9, 2003; 69 FR 2849, Jan. 21, 2004; 69 FR 57861, Sept. 28, 2004; 77 FR 4913, Feb. 1, 2012]

§ 15.119 [Reserved]

§ 15.120 Program blocking technology requirements for television receivers.

(a) Effective July 1, 1999, manufacturers of television broadcast receivers as defined in section 15.3(w) of this chapter, including personal computer systems meeting that definition, must ensure that one-half of their product models with picture screens 33 cm (13 in) or larger in diameter shipped in interstate commerce or manufactured in the United States comply with the provisions of paragraphs (c), (d), and (e) of this section.

NOTE: This paragraph places no restrictions on the shipping or sale of television receivers that were manufactured before July 1999.

(b) All TV broadcast receivers as defined in §15.3(w), including personal computer systems meeting that definition, with picture screens 33 cm (13 in) or larger, measured diagonally, or with

displays in the 16:9 aspect ratio that are 19.8 cm (7.8 in) or greater in height and digital television receivers without an associated display device shipped in interstate commerce or manufactured in the United States shall comply with the provisions of paragraphs (c), (d), and (e) of this section.

(c) *Transmission format.* (1) Analog television program rating information shall be transmitted on line 21 of field 2 of the vertical blanking interval of television signals, in accordance with §73.682(a)(22) of this chapter.

(2) Digital television program rating information shall be transmitted in digital television signals in accordance with §73.682(d) of this chapter.

(d) *Operation.* (1) Analog television receivers will receive program ratings transmitted pursuant to EIA-744: “Transport of Content Advisory Information Using Extended Data Service (XDS)” (incorporated by reference, see §15.38) and EIA-608: “Recommended Practice for Line 21 Data Service” (incorporated by reference, see §15.38). Blocking of programs shall occur when a program rating is received that meets the pre-determined user requirements.

(2) Digital television receivers shall react in a similar manner as analog televisions when programmed to block specific rating categories. Digital television receivers will receive program rating descriptors transmitted pursuant to industry standard EIA/CEA-766-A “U.S. and Canadian Region Rating Tables (RRT) and Content Advisory Descriptors for Transport of Content Advisory Information using ATSC A/65-A Program and System Information Protocol (PSIP),” 2001 (incorporated by reference, see §15.38). Blocking of programs shall occur when a program rating is received that meets the pre-determined user requirements. Digital television receivers shall be able to respond to changes in the content advisory rating system.

(e) All television receivers as described in paragraph (a) of this section shall block programming as follows:

(1) *Channel Blocking.* Channel Blocking should occur as soon as a program rating packet with the appropriate Content Advisory or MPAA rating level is received. Program blocking is