

(e) An earth station using asymmetrical antennas without skew angle adjustment capability must comply with the gain values specified in paragraph (a)(1) of this section, in the plane orthogonal to the to the main plane of the antenna, or, alternatively, in the plane corresponding to the maximum skew angle experienced at any location at which the earth station may be located.

(f) A GSO FSS earth station with an antenna that does not conform to the applicable standards in paragraphs (a) and (b) of this section will be author-

ized only if the applicant demonstrates that the antenna will not cause unacceptable interference. This demonstration must comply with the requirements in § 25.138, § 25.218, § 25.220, § 25.221, § 25.222, § 25.226, or § 25.227, as appropriate.

(g) [Reserved]

(h) The gain of any transmitting antenna in a gateway earth station communicating with NGSO FSS satellites in the 10.7–11.7 GHz, 12.75–13.15 GHz, 13.2125–13.25 GHz, 13.8–14.0 GHz, and/or 14.4–14.5 GHz bands must lie below the envelope defined as follows:

29–25log <sub>10</sub> (θ) .....	dBi	for 1° ≤ θ ≤ 36°.
– 10 .....	dBi	for 36° ≤ θ ≤ 180°.

Where θ and dBi are as defined in paragraph (a)(1) of this section. This envelope may be exceeded by up to 3 dB in 10% of the range of θ angles from ±7–180°.

[48 FR 40255, Sept. 6, 1983, as amended at 50 FR 2675, Jan. 18, 1985; 50 FR 39004, Sept. 26, 1985; 58 FR 13420, Mar. 11, 1993; 66 FR 10630, Feb. 16, 2001; 70 FR 32255, June 2, 2005; 72 FR 50029, Aug. 29, 2007; 73 FR 70901, Nov. 24, 2008; 74 FR 57099, Nov. 4, 2009; 78 FR 8427, Feb. 6, 2013; 78 FR 14927, Mar. 8, 2013; 79 FR 8322, Feb. 12, 2014; 81 FR 55336, Aug. 18, 2016; 83 FR 34491, July 20, 2018]

**§ 25.210 Technical requirements for space stations.**

(a)–(b) [Reserved]

(c) Space station antennas operating in the Direct Broadcast Satellite Service or operating in the Fixed-Satellite Service for reception of feeder links for Direct Broadcast Satellite Service must be designed to provide a cross-polarization isolation such that the ratio of the on-axis co-polar gain to the cross-polar gain of the antenna in the assigned frequency band is at least 27 dB within the primary coverage area.

(d)–(e) [Reserved]

(f) All space stations in the Fixed-Satellite Service operating in any portion of the 3600–4200 MHz, 5091–5250 MHz, 5850–7025 MHz, 10.7–12.7 GHz, 12.75–13.25 GHz, 13.75–14.5 GHz, 15.43–15.63 GHz, 18.3–20.2 GHz, 24.75–25.25 GHz, or 27.5–30.0 GHz bands, including feeder links for other space services, and in the Broadcasting-Satellite Service in

the 17.3–17.8 GHz band (space-to-Earth), shall employ state-of-the-art full frequency reuse, either through the use of orthogonal polarizations within the same beam and/or the use of spatially independent beams. This requirement does not apply to telemetry, tracking, and command operation.

(g)–(h) [Reserved]

(i) 17/24 GHz BSS space station antennas transmitting in the 17.3–17.8 GHz band must be designed to provide a cross-polarization isolation such that the ratio of the on axis co-polar gain to the cross-polar gain of the antenna in the assigned frequency band is at least 25 dB within its primary coverage area.

(j) Space stations operated in the geostationary satellite orbit must be maintained within 0.05° of their assigned orbital longitude in the east/west direction, unless specifically authorized by the Commission to operate with a different longitudinal tolerance, and except as provided in Section 25.283(b) (End-of-life Disposal).

[58 FR 13420, Mar. 11, 1993, as amended at 61 FR 9952, Mar. 12, 1996; 62 FR 5931, Feb. 10, 1997; 62 FR 61457, Nov. 18, 1997; 68 FR 51508, Aug. 27, 2003; 69 FR 54587, Sept. 9, 2004; 70 FR 32256, June 2, 2005; 72 FR 50029, Aug. 29, 2007; 78 FR 8428, Feb. 6, 2013; 79 FR 8323, Feb. 12, 2014; 81 FR 55338, Aug. 18, 2016; 83 FR 34491, July 20, 2018]

**§ 25.211 Analog video transmissions in the FSS.**

(a) [Reserved]

## § 25.212

(b) All conventional C-band analog video transmissions must contain an energy dispersal signal at all times with a minimum peak-to-peak bandwidth set at whatever value is necessary to meet the power flux density limits specified in § 25.208(a) and successfully coordinated internationally and accepted by adjacent U.S. satellite operators based on the use of state of the art space and earth station facilities. All transmissions in frequency bands described in § 25.208(b) and (c) must also contain an energy dispersal signal at all times with a minimum peak-to-peak bandwidth set at whatever value is necessary to meet the power flux density limits specified in § 25.208(b) and (c) and successfully coordinated internationally and accepted by adjacent U.S. satellite operators based on the use of state of the art space and earth station facilities.

(c) All initial analog video transmissions shall be preceded by a video test transmission at an uplink e.i.r.p. at least 10 dB below the normal operating level. The earth station operator shall not increase power until receiving notification from the satellite network control center that the frequency and polarization alignment are satisfactory pursuant to the procedures specified in § 25.272. The stationary earth station operator that has successfully transmitted an initial video test signal to a satellite pursuant to this paragraph is not required to make subsequent video test transmissions if subsequent transmissions are conducted using exactly the same parameters as the initial transmission.

(d) An earth station may be routinely licensed for transmission of full-transponder analog video services in the 5925–6425 MHz band or 14.0–14.5 GHz band provided:

(1) The application includes certification, pursuant to § 25.132(a)(1), of conformance with the antenna performance standards in § 25.209(a) and (b);

(2) For transmission in the 5925–6425 MHz band, the input power into the antenna will not exceed 26.5 dBW; or

(3) For transmission in the 14.0–14.5 GHz band, the input power into the antenna will not exceed 27 dBW.

(e) Applications for authority for analog video uplink transmission in

## 47 CFR Ch. I (10–1–19 Edition)

the 5925–6425 MHz or 14.0–14.5 GHz bands that are not eligible for routine processing under paragraph (d) of this section are subject to the requirements of § 25.220.

[58 FR 13421, Mar. 11, 1993, as amended at 61 FR 9952, Mar. 12, 1996; 62 FR 5931, Feb. 10, 1997; 70 FR 32256, June 2, 2005; 78 FR 8428, Feb. 6, 2013; 79 FR 8323, Feb. 12, 2014; 81 FR 55338, Aug. 18, 2016]

### § 25.212 Narrowband analog transmissions and digital transmissions in the GSO FSS.

(a) Except as otherwise provided by this part, criteria for unacceptable levels of interference caused by other satellite networks shall be established on the basis of nominal operating conditions and with the objective of minimizing orbital separations between satellites.

(b) Emissions with an occupied bandwidth of less than 2 MHz are not protected from interference from wider bandwidth transmissions if the r.f. carrier frequency of the narrowband signal is within  $\pm 1$  MHz of one of the frequencies specified in § 25.211(a).

(c)(1) An earth station that is not subject to licensing under § 25.222, § 25.226, or § 25.227 may be routinely licensed for analog transmissions in the conventional Ku-band or the extended Ku-band with bandwidths up to 200 kHz (or up to 1 MHz for command carriers at the band edge) if the input power spectral density into the antenna will not exceed  $-8$  dBW/4 kHz, and the application includes certification pursuant to § 25.132(a)(1) of conformance with the antenna gain performance requirements in § 25.209(a) and (b).

(2) An earth station that is not subject to licensing under § 25.222, § 25.226, or § 25.227 may be routinely licensed for digital transmission, including digital video transmission, in the conventional Ku-band or the extended Ku-band if input power spectral density into the antenna will not exceed  $-14$  dBW/4 kHz and the application includes certification pursuant to § 25.132(a)(1) of conformance with the antenna gain performance requirements in § 25.209(a) and (b).

(d) An individual earth station that is not subject to licensing under § 25.221 may be routinely licensed for digital