

§ 25.219

EIRP density from all co-frequency earth stations transmitting simultaneously to the same target satellite receiving beam, not resulting from colliding data bursts transmitted pursuant to a contention protocol, will not exceed the off-axis EIRP density limits permissible for a single earth station, as specified in paragraphs (h)(1) through (h)(3) of this section.

(i) Applications for authority for fixed earth station operation in the 5925–6425 MHz or 14.0–14.5 GHz band that do not qualify for routine processing under relevant criteria in this section, § 25.211 or § 25.212 are subject to the requirements in § 25.220.

[81 FR 55339, Aug. 18, 2016]

§ 25.219 [Reserved]

§ 25.220 Non-routine transmit/receive earth station operations.

(a) The requirements in this section apply to applications for, and operation of, earth stations transmitting in the conventional or extended C-bands, the conventional or extended Ku-bands, the 24.75–25.25 GHz band, or the conventional Ka-band that do not qualify for routine licensing under relevant criteria in § 25.138, § 25.211, § 25.212, § 25.218, § 25.221(a)(1) or (a)(3), § 25.222(a)(1) or (a)(3), § 25.226(a)(1) or (a)(3), or § 25.227(a)(1) or (a)(3).

(b) Applications filed pursuant to this section must include the information required by § 25.115(g)(1).

(c) [Reserved]

(d)(1) The applicant must submit the certifications listed in paragraphs (d)(1)(i) through (d)(1)(iv) of this section. The applicant will be authorized to transmit only to the satellite systems included in the coordination agreements referred to in the certification required by paragraph (d)(1)(ii) of this section. The applicant will be granted protection from receiving interference only with respect to the satellite systems included in the coordination agreements referred to in the certification required by paragraph (d)(1)(ii) of this section, and only to the extent that protection from receiving interference is afforded by those coordination agreements.

(i) [Reserved]

47 CFR Ch. I (10–1–19 Edition)

(ii) A statement from the satellite operator that it has coordinated the operation of the subject non-conforming earth station accessing its satellite(s), including its required downlink power density based on the information contained in the application, with all adjacent satellite networks within 6° of orbital separation from its satellite(s), and the operations will operate in conformance with existing coordination agreement for its satellite(s) with other satellite systems, except as set forth in paragraph (d)(4) of this section.

(iii) A statement from the satellite operator that it will include the subject non-conforming earth station operations in all future satellite network coordinations, and

(iv) A statement from the earth station applicant certifying that it will comply with all coordination agreements reached by the satellite operator(s).

(2) Unless the non-routine uplink transmission levels are permitted under a coordination agreement with the space station operator, or unless coordination with the operator is not required pursuant to § 25.140(d)(3) or (d)(4), the operator of an earth station licensed pursuant to this section must reduce its transmitted EIRP density to levels at or within relevant routine limits:

(i) Toward the part of the geostationary orbit arc within one degree of a subsequently launched, two-degree-compliant space station receiving in the same uplink band at an orbital location within six degrees of the earth station's target satellite, and

(ii) Toward a two-degree-compliant space station receiving in the same uplink band at an orbital location more than six degrees away from the target satellite if co-frequency reception by the space station is adversely affected by the non-routine earth station transmission levels.

(3) In the event that a coordination agreement discussed in paragraph (d)(1)(ii) of this section is reached, but that coordination agreement does not address protection from interference for the earth station, that earth station will be protected from interference to the same extent that an