

all cases to improve measurement accuracy, provided the measured power is integrated over the full required measurement bandwidth (i.e., 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

(e) Licensees of terrestrial low-power systems operating in the 2483.5–2495 MHz band shall operate consistent with the technical limits and other requirements specified in § 25.149(c)(4) and (g)(2)–(3).

NOTE TO § 25.254: The preceding rules of § 25.254 are based on cdma2000 and IS-95 system architecture. To the extent that a 1.6/2.4 GHz Mobile-Satellite Service licensee is able to demonstrate that the use of different system architectures would produce no greater potential interference than would be produced as a result of implementing the rules of this section, the licensee may apply for ATC authorization based on another system architecture.

[68 FR 33653, June 5, 2003, as amended at 69 FR 18803, Apr. 9, 2004; 70 FR 19320, Apr. 13, 2005; 73 FR 25592, May 5, 2008; 78 FR 8430, Feb. 6, 2013; 82 FR 8819, Jan. 31, 2017]

§ 25.255 Procedures for resolving harmful interference related to operation of ancillary terrestrial components operating in the 1.5/1.6 GHz and 1.6/2.4 GHz bands.

If harmful interference is caused to other services by ancillary MSS ATC operations, either from ATC base stations or mobile terminals, the MSS ATC operator must resolve any such interference. If the MSS ATC operator claims to have resolved the interference and other operators claim that interference has not been resolved, then the parties to the dispute may petition the Commission for a resolution of their claims.

[68 FR 33653, June 5, 2003, as amended at 78 FR 8267, Feb. 5, 2013]

§ 25.256 Special Requirements for operations in the 3.65–3.7 GHz band.

Upon request from a terrestrial licensee authorized under subpart Z, part 90 that seeks to place base and fixed stations in operation within 150 km of a primary earth station, licensees of earth stations operating on a primary basis in the Fixed-Satellite Service in the 3.65–3.7 GHz band must negotiate in good faith with that terrestrial licensee to arrive at mutually agreeable operating parameters to prevent unacceptable interference.

[70 FR 24725, May 11, 2005, as amended at 78 FR 8430, Feb. 6, 2013]

§ 25.257 Special requirements for NGSO MSS operations in the 29.1–29.25 GHz band regarding LMDS.

(a) Non-geostationary Mobile-Satellite Service (NGSO MSS) operators shall be licensed to use the 29.1–29.25 GHz band for Earth-to-space transmissions from feeder link earth station complexes. A “feeder link earth station complex” may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by a NGSO MSS licensee or applicants pursuant to § 101.147.

(b) A maximum of seven (7) feeder link earth station complexes in the contiguous United States, Alaska and Hawaii may be placed into operation, in the largest 100 MSAs, in the band 29.1–29.25 GHz in accordance with § 25.203 and § 101.147 of this chapter.

(c) One of the NGSO MSS operators licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of eight feeder link earth station complexes that transmit in the 29.1–29.25 GHz band. The other NGSO MSS operator licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of two feeder link earth station complexes that transmit in the 29.1–29.25 GHz band.

(d) Additional NGSO MSS operators may be licensed in this band if the additional NGSO MSS operator shows that its system can share with the existing NGSO MSS systems.

§ 25.258

(e) All NGSO MSS operators shall cooperate fully and make reasonable efforts to identify mutually acceptable locations for feeder link earth station complexes. In this regard, any single NGSO MSS operator may identify only one feeder-link earth station complex protection zone in each category identified in §101.147(y)(2) of this chapter until the other NGSO MSS operator has been given an opportunity to select a location from the same category.

[61 FR 44181, Aug. 28, 1996, as amended at 78 FR 8430, Feb. 6, 2013; 81 FR 55348, Aug. 18, 2016]

§ 25.258 Sharing between NGSO MSS feeder-link stations and GSO FSS services in the 29.25–29.5 GHz band.

(a) Operators of NGSO MSS feeder link earth stations and GSO FSS earth stations in the band 29.25 to 29.5 GHz where both services have a co-primary allocation shall cooperate fully in order to coordinate their systems. During the coordination process both service operators shall exchange the necessary technical parameters required for coordination.

(b) Licensed GSO FSS earth stations in the vicinity of operational NGSO MSS feeder-link earth station complexes must, to the maximum extent possible, operate with frequency/polarization selections that will minimize unacceptable interference with reception of GSO FSS and NGSO MSS uplink transmissions in the 29.25–29.5 GHz band. Earth station licensees operating with GSO FSS systems shall be capable of providing earth station locations to support coordination of NGSO MSS feeder link stations under paragraphs (a) and (c) of this section. Operation of ubiquitously deployed GSO FSS earth stations in the 29.25–29.5 GHz frequency band shall conform to the rules contained in §25.138.

(c) Applicants for authority to use the 29.25–29.5 GHz band for NGSO MSS feeder uplinks will have to demonstrate that their systems can share with GSO FSS and NGSO MSS systems that have been authorized for operation in that band.

[67 FR 37336, May 29, 2002, as amended at 68 FR 16967, Apr. 8, 2003; 81 FR 55348, Aug. 18, 2016]

47 CFR Ch. I (10–1–19 Edition)

§ 25.259 Time sharing between NOAA meteorological satellite systems and non-voice, non-geostationary satellite systems in the 137–138 MHz band.

(a) The space stations of a non-voice, non-geostationary Mobile-Satellite Service (NVNG MSS) system time-sharing downlink spectrum in the 137–138 MHz band with National Oceanic and Atmospheric Administration (NOAA) satellites shall not transmit signals into the “protection areas” of the NOAA satellites.

(1) With respect to transmission in the 137.333–137.367 MHz, 137.485–137.515 MHz, 137.605–137.635 MHz, and 137.753–137.787 MHz bands, the protection area for a NOAA satellite is the area on the Earth’s surface in which the NOAA satellite is in line of sight from the ground at an elevation angle of five degrees or more above the horizon. No NVNG MSS satellite shall transmit in these bands when it is in line of sight at an elevation angle of zero degrees or more from any point on the ground within a NOAA satellite’s protected area for that band.

(2) With respect to transmission in the 137.025–137.175 MHz and 137.825–138 MHz bands, the protection area for a NOAA satellite is the area on the Earth’s surface in which the NOAA satellite is in line of sight from the ground at any elevation angle above zero degrees. No NVNG MSS satellite shall transmit in these bands when at a line-of-sight elevation angle of zero degrees or more from any point on the ground within a NOAA satellite’s protected area for that band. In addition, such an NVNG MSS satellite shall cease transmitting when it is at an elevation angle of less than zero degrees from any such point, if reasonably necessary to protect reception of the NOAA satellite’s signal.

(3) An NVNG MSS licensee is responsible for obtaining the ephemeris data necessary for compliance with these restrictions. The ephemeris information must be updated system-wide on at least a weekly basis. For calculation required for compliance with these restrictions an NVNG MSS licensee shall use an orbital propagator algorithm with an accuracy equal to or greater