

§ 90.557

§ 90.557 Secondary fixed signaling operations.

Trunked and conventional 700 MHz narrowband systems may conduct fixed ancillary signaling and data transmissions subject to the following requirements:

(a) Operations are permitted only on:

(1) Narrowband State License channels specified in § 90.531(b)(5), subject to the discretion of the relevant State licensee; and

(2) Narrowband General Use channels specified in § 90.531(b)(6), subject to the discretion of the regional planning committee.

(b) All operations must be on a secondary, non-interference basis to the primary mobile operation of any other licensee.

(c) The output power at the remote site must not exceed 30 watts.

(d) Automatic means must be provided to deactivate the remote transmitter in the event the carrier remains on for a period in excess of three minutes.

(e) Operational fixed stations authorized pursuant to this section are exempt from the requirements of §§ 90.425, 90.429, and 90.559.

(f) Any operations undertaken in a shared use environment must be conducted pursuant to an agreement between the licensee and each participant, as set forth in § 90.179.

[79 FR 39341, July 10, 2014]

§ 90.559 Station Identification.

(a) Conventional systems of communication shall be identified in accordance with existing regulations governing such matters.

(b) Trunked systems of communication, except as noted in paragraph (c) of this section, shall be identified through the use of an automatic device which transmits the call sign of the base station facility at 30 minute intervals. Such station identification shall be made on the lowest frequency in the base station trunk group assigned to the licensee. Should this frequency be in use at the time station identification is required, such identification may be made at the termination of the communication in progress on this frequency. Identification may be made by

47 CFR Ch. I (10–1–19 Edition)

voice or International Morse Code. When the call sign is transmitted in International Morse Code, it must be at a rate of between 15 to 20 words per minute and by means of tone modulation of the transmitter, the tone frequency being between 800 and 1000 hertz.

(c) Stations operating in the 769–775/799–805 MHz band that are licensed on an exclusive basis, and normally employ digital signals for the transmission of data, text, control codes, or digitized voice may also be identified by digital transmission of the call sign. A licensee that identifies its station in this manner must provide the Commission, upon its request, information sufficient to decode the digital transmission and ascertain the call sign transmitted.

[79 FR 39341, July 10, 2014]

Subpart S—Regulations Governing Licensing and Use of Frequencies in the 806–824, 851–869, 896–901, and 935–940 MHz Bands

§ 90.601 Scope.

This subpart sets out the regulations governing the licensing and operations of all systems operating in the 806–824/851–869 MHz and 896–901/935–940 MHz bands. It includes eligibility requirements, and operational and technical standards for stations licensed in these bands. It also supplements the rules regarding application procedures contained in part 1, subpart F of this chapter. The rules in this subpart are to be read in conjunction with the applicable requirements contained elsewhere in this part; however, in case of conflict, the provisions of this subpart shall govern with respect to licensing and operation in these frequency bands.

[63 FR 68967, Dec. 14, 1998]

APPLICATION FOR AUTHORIZATIONS

§ 90.603 Eligibility.

The following persons are eligible for licensing in the 806–824 MHz, 851–869 MHz, 896–901 MHz, and 935–940 MHz Bands.