

(i) Up to 30 meters, the AFC system must use the free space path-loss model.

(ii) More than 30 meters and up to and including one kilometer, the AFC system must use the Wireless World Initiative New Radio phase II (WINNER II) model. The AFC system must use site-specific information, including buildings and terrain data, for determining the line-of-sight/non-line-of-sight path component in the WINNER II model, where such data is available. For evaluating paths where such data is not available, the AFC system must use a probabilistic model combining the line-of-sight path and non-line-of-sight path into a single path-loss as follows:

$$\text{Path-loss (L)} = \sum_i P(i) * L_i = P_{\text{LOS}} * L_{\text{LOS}} + P_{\text{NLOS}} * L_{\text{NLOS}},$$

where P_{LOS} is the probability of line-of-sight, L_{LOS} is the line-of-sight path loss, P_{NLOS} is the probability of non-line-of-sight, L_{NLOS} is the non-line-of-sight path loss, and L is the combined path loss. The WINNER II path loss models include a formula to determine P_{LOS} as a function of antenna heights and distance. P_{NLOS} is equal to $(1 - P_{\text{LOS}})$. In all cases, the AFC system will use the correct WINNER II parameters to match the morphology of the path between a standard power access point and a fixed microwave receiver (i.e., Urban, Suburban, or Rural).

(iii) More than one kilometer, the AFC system must use Irregular Terrain Model (ITM) combined with the appropriate clutter model. To account for the effects of clutter, such as buildings and foliage, that the AFC system must combine the ITM with the ITU-R P.2108-0 (06/2017) clutter model for urban and suburban environments and the ITU-R P.452-16 (07/2015) clutter model for rural environments. The AFC system should use the most appropriate clutter category for the local morphology when using ITU-R P.452-16. However, if detailed local information is not available, the "Village Centre" clutter category should be used. The AFC system must use 1 arc-second digital elevation terrain data and, for locations where such data is not available, the most granular available digital elevation terrain data.

(2) Interference Protection Criteria:

(i) The AFC system must use -6 dB I/N as the interference protection criteria in determining the size of the co-channel exclusion zone where I (interference) is the co-channel signal from the standard power access point or fixed client device at the fixed microwave service receiver, and N (noise) is background noise level at the fixed microwave service receiver.

(ii) The AFC system must use -6 dB I/N as the interference protection criteria in determining the size of the adjacent channel exclusion zone, where I (interference) is the signal from the standard power access point or fixed client device's out of channel emissions at the fixed microwave service receiver and N (noise) is background noise level at the fixed microwave service receiver. The adjacent channel exclusion zone must be calculated based on the emissions requirements of paragraph (b)(6) of this section.

(m) *Incumbent Protection by AFC system: Radio Astronomy Services.* The AFC system must enforce an exclusion zones to the following radio observatories that observe between 6650-6675.2 MHz: Arecibo Observatory, the Green Bank Observatory, the Very Large Array (VLA), the 10 Stations of the Very Long Baseline Array (VLBA), the Owens Valley Radio Observatory, and the Allen Telescope Array. The exclusion zone sizes are based on the radio line-of-sight and determined using $\frac{4}{3}$ earth curvature and the following formula:

$$\text{dkm}_{\text{los}} = 4.12 * (\text{sqrt}(\text{Htx}) + \text{sqrt}(\text{Hrx})),$$

where Htx is the height of the unlicensed standard power access point or fixed client device and Hrx is the height of the radio astronomy antenna in meters above ground level. Coordinate locations of the radio observatories are listed in section 2.106, notes US 131 and US 385 of this part.

(n) *Incumbent Protection by AFC system: Fixed-Satellite Services.* Standard power access points and fixed client devices located outdoors must limit their maximum e.i.r.p. at any elevation angle above 30 degrees as measured