

megahertz at the receiver of a co-channel base station that is within its applicable height benchmark, then the licensee of the base station that exceeds its applicable height benchmark shall either limit the undesired signal at the receiver of the protected base station to $-107\text{dBm}/5.5$ megahertz or less or reduce the height of its transmission antenna to no more than the height benchmark. If the interfering base station has been modified to increase the EIRP transmitted in the direction of the protected base station, it shall be deemed to have commenced operations on the date of such modification. Such corrective action shall be completed no later than:

(i) 24 hours after receiving such notification, if the base station that exceeds its height benchmark commenced operations after the station that is within its applicable height benchmark; or

(ii) 90 days after receiving such notification, if the base station that exceeds its height commenced operations prior to the station that is within its applicable height benchmark. For purposes of this section, if the interfering base station has been modified to increase the EIRP transmitted in the direction of the victim base station, it shall be deemed to have commenced operations on the date of such modification.

(d) *No Protection from a transmitting antenna not exceeding the height benchmark.* The licensee of a base station transmitting antenna less than or equal to its applicable height benchmark shall not be required pursuant to paragraph (c) of this section to limit that antenna's undesired signal level to $-107\text{dBm}/5.5$ megahertz or less at the receiver of any co-channel base station.

(e) *No protection for a receiving-antenna exceeding the height benchmark.* The licensee of a base station receive antenna that exceeds its applicable height benchmark shall not be entitled pursuant to paragraph (c) of this section to insist that any co-channel base station limit its undesired signal level to $-107\text{dBm}/5.5$ megahertz or less at the receiver.

(f) *Information exchange.* A BRS/EBS licensee shall provide the geographic coordinates, the height above ground

level of the center of radiation for each transmit and receive antenna, and the date transmissions commenced for each of the base stations in its GSA within 30 days of receipt of a request from a co-channel BRS/EBS licensee with an operational base station located in a proximate GSA. Information shared pursuant to this section shall not be disclosed to other parties except as required to ensure compliance with this section.

[69 FR 72034, Dec. 10, 2004, as amended at 70 FR 1190, Jan. 6, 2005; 71 FR 35191, June 19, 2006; 73 FR 26041, May 8, 2008]

§ 27.1222 Operations in the 2568–2572 and 2614–2618 bands.

All operations in the 2568–2572 and 2614–2618 MHz bands shall be secondary to adjacent-channel operations. Stations operating in the 2568–2572 and 2614–2618 MHz must not cause interference to licensees in operation in the LBS, MBS, and UBS and must accept any interference from any station operating in the LBS, MBS, and UBS in compliance with the rules established in this subpart. Stations operating in the 2568–2572 and 2614–2618 bands may cause interference to stations in operation in the LBS, MBS, and UBS if the affected licensees consent to such interference.

RELOCATION PROCEDURES FOR THE 2150–2160/62 MHz BAND

SOURCE: Sections 27.1250 through 27.1255 appear at 71 FR 29840, May 24, 2006, unless otherwise noted.

§ 27.1250 Transition of the 2150–2160/62 MHz band from the Broadband Radio Service to the Advanced Wireless Service.

The 2150–2160/62 MHz band has been allocated for use by the Advanced Wireless Service (AWS). The rules in this section provide for a transition period during which AWS licensees may relocate existing Broadband Radio Service (BRS) licensees using these frequencies to their assigned frequencies in the 2496–2690 MHz band or other media.

(a) AWS licensees and BRS licensees shall engage in mandatory negotiations for the purpose of agreeing to

terms under which the BRS licensees would:

(1) Relocate their operations to other frequency bands or other media; or alternatively

(2) Accept a sharing arrangement with the AWS licensee that may result in an otherwise impermissible level of interference to the BRS operations.

(b) If no agreement is reached during the mandatory negotiation period, an AWS licensee may initiate involuntary relocation procedures. Under involuntary relocation, the incumbent is required to relocate, provided that the AWS licensee meets the conditions of § 27.1252.

(c) Relocation of BRS licensees by AWS licensees will be subject to a three-year mandatory negotiation period. BRS licensees may suspend the running of the three-year negotiation period for up to one year if the BRS licensee cannot be relocated to comparable facilities at the time the AWS licensee seeks entry into the band.

§ 27.1251 Mandatory negotiations.

(a) Once mandatory negotiations have begun, a BRS licensee may not refuse to negotiate and all parties are required to negotiate in good faith. Good faith requires each party to provide information to the other that is reasonably necessary to facilitate the relocation process. The BRS licensee is required to cooperate with an AWS licensee's request to provide access to the facilities to be relocated, other than the BRS customer location, so that an independent third party can examine the BRS system and prepare an appraisal of the costs to relocate the incumbent. In evaluating claims that a party has not negotiated in good faith, the FCC will consider, *inter alia*, the following factors:

(1) Whether the AWS licensee has made a bona fide offer to relocate the BRS licensee to comparable facilities in accordance with § 27.1252(b);

(2) If the BRS licensee has demanded a premium, the type of premium requested (*e.g.*, whether the premium is directly related to relocation, such as analog-to-digital conversions, versus other types of premiums), and whether the value of the premium as compared to the cost of providing comparable fa-

cilities is disproportionate (*i.e.*, whether there is a lack of proportion or relation between the two);

(3) What steps the parties have taken to determine the actual cost of relocation to comparable facilities;

(4) Whether either party has withheld information requested by the other party that is necessary to estimate relocation costs or to facilitate the relocation process.

(b) Any party alleging a violation of our good faith requirement must attach an independent estimate of the relocation costs in question to any documentation filed with the Commission in support of its claim. An independent cost estimate must include a specification for the comparable facility and a statement of the costs associated with providing that facility to the incumbent licensee.

(c) Mandatory negotiations will commence for each BRS licensee when the AWS licensee informs the BRS licensee in writing of its desire to negotiate. Mandatory negotiations will be conducted with the goal of providing the BRS licensee with comparable facilities, defined as facilities possessing the following characteristics:

(1) *Throughput*. Communications throughput is the amount of information transferred within a system in a given amount of time. System is defined as a base station and all end user units served by that base station. If analog facilities are being replaced with analog, comparable facilities may provide a comparable number of channels. If digital facilities are being replaced with digital, comparable facilities provide equivalent data loading bits per second (bps).

(2) *Reliability*. System reliability is the degree to which information is transferred accurately within a system. Comparable facilities provide reliability equal to the overall reliability of the BRS system. For digital systems, reliability is measured by the percent of time the bit error rate (BER) exceeds a desired value, and for analog or digital video transmission, it is measured by whether the end-to-end transmission delay is within the required delay bound. If an analog system is replaced with a digital system, only the resulting frequency response,