

the requirements to be certified under subpart B of this part (FRS).

**§ 95.1763 GMRS channels.**

The GMRS is allotted 30 channels—16 main channels and 14 interstitial channels. GMRS stations may transmit on any of the channels as indicated below.

(a) *462 MHz main channels.* Only mobile, hand-held portable, repeater, base and fixed stations may transmit on these 8 channels. The channel center frequencies are: 462.5500, 462.5750, 462.6000, 462.6250, 462.6500, 462.6750, 462.7000, and 462.7250 MHz.

(b) *462 MHz interstitial channels.* Only mobile, hand-held portable and base stations may transmit on these 7 channels. The channel center frequencies are: 462.5625, 462.5875, 462.6125, 462.6375, 462.6625, 462.6875, and 462.7125 MHz.

(c) *467 MHz main channels.* Only mobile, hand-held portable, control and fixed stations may transmit on these 8 channels. Mobile, hand-held portable and control stations may transmit on these channels only when communicating through a repeater station or making brief test transmissions in accordance with § 95.319(c). The channel center frequencies are: 467.5500, 467.5750, 467.6000, 467.6250, 467.6500, 467.6750, 467.7000, and 467.7250 MHz.

(d) *467 MHz interstitial channels.* Only hand-held portable units may transmit on these 7 channels. The channel center frequencies are: 467.5675, 467.5875, 467.6125, 467.6375, 467.6625, 467.6875, and 467.7125 MHz.

**§ 95.1765 GMRS frequency accuracy.**

Each GMRS transmitter type must be designed to comply with the frequency accuracy requirements in this section under normal operating conditions. Operators of GMRS stations must also ensure compliance with these requirements.

(a) The carrier frequency of each GMRS transmitter transmitting an emission with an occupied bandwidth greater than 12.5 kHz must remain within 5 parts-per-million (ppm) of the channel center frequencies listed in § 95.1763 under normal operating conditions.

(b) The carrier frequency of each GMRS transmitter transmitting an emission with an occupied bandwidth

of 12.5 kHz or less must remain within 2.5 ppm of the channel center frequencies listed in § 95.1763 under normal operating conditions.

**§ 95.1767 GMRS transmitting power limits.**

This section contains transmitting power limits for GMRS stations. The maximum transmitting power depends on which channels are being used and the type of station.

(a) *462/467 MHz main channels.* The limits in this paragraph apply to stations transmitting on any of the 462 MHz main channels or any of the 467 MHz main channels. Each GMRS transmitter type must be capable of operating within the allowable power range. GMRS licensees are responsible for ensuring that their GMRS stations operate in compliance with these limits.

(1) The transmitter output power of mobile, repeater and base stations must not exceed 50 Watts.

(2) The transmitter output power of fixed stations must not exceed 15 Watts.

(b) *462 MHz interstitial channels.* The effective radiated power (ERP) of mobile, hand-held portable and base stations transmitting on the 462 MHz interstitial channels must not exceed 5 Watts.

(c) *467 MHz interstitial channels.* The effective radiated power (ERP) of hand-held portable units transmitting on the 467 MHz interstitial channels must not exceed 0.5 Watt. Each GMRS transmitter type capable of transmitting on these channels must be designed such that the ERP does not exceed 0.5 Watt.

**§ 95.1769 [Reserved]**

**§ 95.1771 GMRS emission types.**

Each GMRS transmitter type must be designed to satisfy the emission capability rules in this section. Operation of GMRS stations must also be in compliance with these rules.

(a) Each GMRS transmitter type must have the capability to transmit F3E or G3E emissions.

(b) Only emission types A1D, F1D, G1D, H1D, J1D, R1D, A3E, F3E, G3E,